=> d his

(FILE 'USPAT' ENTERED AT 10:22:56 ON 27 JUN 1997)

                        SET PAGE SCROLL
L1   65 S WWW OR (WORLD WIDE WEB)
L2   43 S (AUTOMATIC? OR DYNAMIC?) (3A) (GENERAT? OR CREAT?) (3A) PAG
L3   3245 S (BASED OR DEPEND?) (5A) REQUEST?
L4   0 S L2 (P) L3
L5   2 S L2 AND L3
L6   0 S L1 AND L2
L7   0 S PAGE SERVER#
L8   668 S (PLURALITY OR MULTIPLE OR DUAL) (3A) SERVER#
L9   3 S L1 AND L8
L10   28003 S (CONCURRENT? OR SIMULTANEOUS?) (5A) PROCESS?
L11   5 S L1 AND L10
L12   8 S L2 AND L10
L13   1 S L2 (P) L10
L14   18 S L8 (P) L10
L15   0 S PSEDO (2A) SERVER#
L16   9 S PSEUDO (2A) SERVER#
L17   0 S L3 (P) L14
L18   7 S L14/AB,CLM
L19   6506 S (GENERAT? (3A) REQUEST#)
L20   10973 S (RECEIV? (3A) REQUEST#)
L21   1719 S (ROUT? (3A) REQUEST#)
L22   41032 S (RELEAS? OR RELINQUISH?) (3A) (SYSTEM OR BUS OR CONTROL?)
L23   8776 S (PROCESS? (3A) REQUEST#)
L24   652 S (AUTOMATIC? OR DYNAMIC?) (3A) (GENERAT? OR CREAT?) (3A) (BA
L25   1277 S L19 (P) L20
L26   32 S L21 (P) L25
L27   0 S L26 (P) L22
L28   4 S L26 AND L22
L29   12 S L23 (P) L26
L30   4 S L22 AND L29
L31   4 S L28 OR L30
L32   5 S L23 (P) L24

        FILE 'JPOABS' ENTERED AT 12:09:09 ON 27 JUN 1997

L33   1 S L1
L34   9 S L2
L35   1740 S L3
L36   1740 S L3
L37   0 SS L4
L38   8 S L8
L39   5612 S L10
L40   6 S L16
L41   2706 S L19
L42   5843 S L20
L43   122 S L21
L44   4800 S L22
L45   5152 S L23
L46   138 S L24
L47   297 S L25
L48   0 S L26
L49   0 S L29
L50   1 S L44 (P) L47
L51   1 S L35 (P) L46

FILE 'EPOABS' ENTERED AT 12:15:54 ON 27 JUN 1997

```
L52           0 S L1
L53           5 S L2
L54         205 S L3
L55           0 S L4
L56          74 S L8
L57        2379 S L10
L58           1 S L16
L59         383 S L19
L60         727 S L20
L61          53 S L21
L62        5034 S L22
L63         678 S L23
L64          52 S L24
L65          69 S L25
L66           1 S L26
```

=> d 1-4 ti,kwic

US PAT NO: 5,613,071 [IMAGE AVAILABLE]   L30: 1 of 4
TITLE: Method and apparatus for providing remote memory access in a
                 distributed memory multiprocessor system

DETDESC:

DETD(139)

 Lock .   .   . NIC returns the value Read from memory to the requesting node
and immediately Writes "0" to the location. The NIC **releases** the **bus** lock
on the Write operation. A non-zero value returned to the requesting node
indicates the lock was successfully obtained. A.   .   .

CLAIMS:

CLMS(1)

 What .   .   .

and from the processor and the memory; and a remote memory access controller,
coupled to the bus, for detecting and **processing** remote memory access
requests, said remote memory access controller
comprising:
 (a) a remote memory access request mapping module coupled to the processor
  bus for detecting a remote memory access **request**;
 (b) a **processor** bus interface coupled to the proc
essor bus and the remote
  memory access request mapping module for providing an interface between.   .
  . processor and the remote memory access controller;
 (c) a packet generator coupled to the processor bus interface, said
  processor bus interface **receiving** a remote memory **request**, accessing a
   route table for network route information, and **generating** a 7mrequest
  packet having said network **route** information, said **request** packet
  suitable for transmission on the network;
 (d) a packet decoder coupled to the processor bus interface for decoding
  response packets.   .   . network protocol interface coupled to the network,
  said network protocol interface having at least two lanes, said network
  protocol interface **receiving request** packets from the network and
  sending response packets to the network and detecting network errors in the
  response and request.   .   .

US PAT NO: 4,064,561 [IMAGE AVAILABLE]   L30: 2 of 4
TITLE: CRT key station which is responsive to centralized control

DETDESC:

DETD(55)

 There are four external interrupt request signals, INR1-INR4, and five
internally **generated** interrupt **request** signals. These signals are
interpreted by the central **processing** unit as a **request** by the issuing
device to designate the location of an interrupt vector when the central
processing unit has completed executing.   .   . otherwise begin executing
anoyther instruction. The designated interrupt vector represents the address
of the initial instruction of a program or **routine** for **processing**
interrupt **requests** for the requesting device. Neithe
r external nor internal
interrupt requests will be honored while the central processing unit program

has. . . flip-flop associated with each level is set to the "on" state to
enable that level. Whenever one or more interrupt **requests** are **received**
on levels that are armed, each of these levels is compared with the current
processor level. The highest enabled interrupt. . .

DETDESC:

DETD(57)

Upon . . . in practice the potential bus masters are normally designed to
make only one direct memory access for each grant of **bus** **control** and then
relinquish **bus** **control** while information recei
ved from memory during
the direct memory access is processed. A new bus request is then initiated
each. . .

DETDESC:

DETD(137)
which . . . continuously generated on the bus lines until a requested
interrupt has been processed or until the KMUX is ready to **relinquish** **bus**
mastership as required for the predetermined protocol of the system data bus
12. As the CPU 16 terminates the grant. . . As flip-flop 1344 resets,
signal 1GACK returns to logic one and either a granted interrupt is
terminated or a granted **bus** mastership is **relinquished**. Flip-flops 1340
and 1344 which are normally in the reset state have their complementing clear
inputs connected to the system. . .

US PAT NO: 4,047,158 [IMAGE AVAILABLE]   L30: 3 of 4
TITLE: Peripheral processing system

DETDESC:

DETD(55)

There are four external interrupt request signals, INR1-INR4, and five
internally **generated** interrupt **request** signals. These signals are
interpreted by the central **processing** unit as a **request** by the issuing
device to designate the location of an interrupt vector when the central
processing unit has completed executing. . . otherwise begin executing
another instruction. The designated interrupt vector represents the address
of the initial instruction of a program or **routine** for **processing**
interrupt **requests** for the requesting device. Neithe
r external nor internal
interrupt requests will be honored while the central processing unit program
has. . . flip-flop associated with each level is set to the on state to
enable that level. Whenever one or more interrupt **requests** are **received**
on levels that are armed, each of these levels is compared with the current
processor level. The highest enabled interrupt. . .

DETDESC:

DETD(57)

Upon . . . in practice the potential bus masters are normally designed to
make only one direct memory access for each grant of **bus** **control** and then
relinquish **bus** **control** while information recei
ved from memory during
the direct memory access is processed. A new bus request is then initiated
each. . .

=> d 19 1-3 ti,kwic

US PAT NO: 5,640,193 [IMAGE AVAILABLE]   L9: 1 of 3
TITLE: Multimedia service access by reading marks on an object

DETDESC:

DETD(17)

  Communication . . . in a similar way as the well-known Universal Resource
Locator (URL) identifiers in NCSA Mosaic (Internet client access software for
World Wide Web), only they would be read from paper (instead of typed
into an application) or invisibly linked to on-screen buttons. Because. . .

CLAIMS:

CLMS(18)

  18. .   .   .
under the control of the user, the request command to said multimedia server
  location over the established connection, said multimedia **server** location
  containing a **plurality** of video previews,
selecting, at the multimedia server, the multimedia service having the
  information using the received request command, and
transmitting a.   .   .

CLAIMS:

CLMS(22)

  22. A method for providing an instruction-video-program-on-demand service to
a user, comprising the steps of
  providing a multimedia **server** having a **plurality** of video programs
  accessible by a user in response to a request command received from the
  user,
establishing a communication connection.   .   .

US PAT NO: 5,600,831 [IMAGE AVAILABLE]   L9: 2 of 3
TITLE: Apparatus and methods for retrieving information by modifying
                 query plan based on description of information sources

DETDESC:

DETD(9)

  User .   .   . working with these high-level concepts, the user is unburdened
with the details of the location and distribution of information across
multiple remote information **servers**.

DETDESC:

DETD(80)

  A .   .   . definitions of the concepts and the information available about
the object. For example, suppose the concept hierarchy included the concepts
www.sub.-- site and ftp.sub.-- site (which is defined to be the subconcept
of **www**.sub.-- site whose URL attribute begins with the string ftp :). If
the user creates an object as an instance of **www**.sub.-- site with its URL
as ftp://research.att.com, then the system will also classify it as an
instance of ftp.sub.-- site; this.   .   .

US PAT NO: 5,572,643 [IMAGE AVAILABLE]   L9: 3 of 3
TITLE: Web browser with dynamic display of information objects during
               linking

SUMMARY:

BSUM(4)

 The . . . allow for simple graphical user interface (GUI)-based access to
network servers, which support documents formatted as so-called "web pages".
The "**World Wide Web**" (**WWW**) is that collection of servers of the
Internet that utilize the Hypertext Transfer Protocol (HTTP). HTTP is a known
application. . .

DETDESC:

DETD(3)

 The "**World Wide Web**" (**WWW**) is that collection of servers of the
Internet that utilize the Hypertext Transfer Protocol (HTTP). HTTP is a known
application. . .

DETDESC:

DETD(7)

 HyperText . . . the reader is directed to the HTML Reference Manual,
published by Sandia National Laboratories, and available on the Internet at
"http://**www**.sandia.gov/sci.sub.-- compute/html.ref.html" or the HTML Quick
Reference, published by the University of Kansas, and available on the
Internet at "http://kuhttp.cc.u.kans.edu/lynx.sub.-- help/HTML.sub.--. . .

DETDESC:

DETD(12)

 FIG. 4 shows the browser navigation tool prior to download of the U.S.
Patent and Trademark Office page (available at http://**www**.uspto.gov). FIG.
5 shows the web page as it exists on the display. This web page has various
links including "Welcome. . .

CLAIMS:

CLMS(9)

 9. A method of browsing the **World Wide Web** of the Internet using a
client machine supporting a browser, comprising the steps of:
 storing an information object;
 activating a link. . .

CLAIMS:

CLMS(19)

 19. A method of browsing in a computer network having a **plurality** of
servers that support hypert
ext objects, comprising the steps of:
 storing a plurality of information objects at a client machine having a. .

=> d 15 1-2 ti,kwic

US PAT NO: 5,638,438 [IMAGE AVAILABLE]   L5: 1 of 2
TITLE: System and method for **automatically** **creating** new **pages**
                  in a touch screen based telephony product having a
                  hierarchical repertory
TITLE: System and method for **automatically** **creating** new **pages**
                  in a touch screen based telephony product having a
                  hierarchical repertory

ABSTRACT:
Automatic expansion of a hierarchical repertory that is maintained by a touch
screen **based** product to accommodate a user **request** to add an entry to a
touch screen display page that has reached its capacity of entries is
discussed. Such.   .   .

SUMMARY:

BSUM(3)

  The .   .   . relates generally to touch screen based telephony products, and
more particularly to a touch screen based telephony product wherein new
pages are **automatically** **created** in a hierarchical repertory of
telephone numbers.

SUMMARY:

BSUM(29)

  Thus, .   .   . hierarchical repertory maintained by a touch screen based
telephone. More particularly, what is required is a system and method for
automatically **creating** a new display **page** and expanding the
hierarchical repertory for the purpose of accommodating such a user request.

SUMMARY:

BSUM(31)

  The .   .   . is directed to a system and method for automatically expanding
a hierarchical repertory that is maintained by a touch screen **based** product
to accommodate a user **request** to add an entry to a touch screen display
page that has reached its capacity of entries. The present invention.   .   .

DETDESC:

DETD(2)

  The .   .   . is directed to a system and method for automatically expanding
a hierarchical repertory that is maintained by a touch screen **based** product
to accommodate a user **request** to add an entry (such as a telephone number
button) to a full touch screen display page. User data is.   .   .

DETDESC:

DETD(37)

  Accordingly, .   .   . present invention represents a system and method for
automatically expanding a hierarchical repertory that is maintained by a
touch screen **based** product to accommodate a user **request** to add an entry
to a full touch screen display page. Such expansion occurs automatically

without any user interaction. Thus,. . .

CLAIMS:

CLMS(1)

What is claimed is:

1. A method of automatically expanding a hierarchical repertory that is
maintained by a touch screen **based** product to accommodate a user **request**
to add an entry to a selected one of at least one touch screen display page,
the selected touch screen. . .

CLAIMS:

CLMS(2)

2. The method of claim 1, further comprising the steps of:
automatically creating a new display **page**;
automatically associating one of a second new menu button with said first
  node if said first node has at least one. . .

CLAIMS:

CLMS(6)   .

6. The system of claim 5 wherein said control logic further comprises:
means for enabling said processor to **automatically create** a new display
  page;
means for enabling said processor to automatically associate one of a second
  new menu button with said first node if said. . .

CLAIMS:

CLMS(10)

10. A system of automatically expanding a hierarchical repertory that is
maintained by a touch screen **based** product to accommodate a user **request**
to add an entry to a selected touch screen display page that has reached its
capacity of entries, comprising:
  button. . .

CLAIMS:

CLMS(11)

11. The system of claim 10 further comprising:
means for **automatically creating** a new display **page**;
means for automatically associating one of a second new menu button with
  said first node if said first node has at. . .

US PAT NO: 4,814,763 [IMAGE AVAILABLE]   L5: 2 of 2
TITLE: Paging terminal apparatus with page forwarding capability and
               methodology thereof

DETDESC:

DETD(29)

After . . . prompt state. However, if there is a forwarding request

contained in the acknowledgment, the paging controller selects a forwarding address **based** upon this **request** from the subscriber list at step 115, and at step 116, the controller updates the active page file with a. . .

DETDESC:

DETD(35)

 Paging . . . to the pager. Once the address has been detected at step 202, the paging address decoder 58 at step 203 **generates** an appropriate **pager** **automatic** acknowledge back response (he
reinafter "PACK") consisting
of particular coded words, which then keys the transmitter 52 which is modulated with. . .

=>

```
? ds

Set        Items      Description
S1         9996       (WEB (2N) SERVER)
S2          565       (PAGE (2N) SERVER)
S3          229       S1 AND S2
S4          700       (PAGE (2N) SERVER?)
S5          255       S1 AND S4
S6          127       S1 (S) S4
S7         8043       (USER? (3N) REQUEST?)
S8          238       (INTERCEPT? (3N) REQUEST?)
S9         1529       (ROUT? (3N) REQUEST?)
S10           7       S1 (S) S8
S11           2       S4 (S) S9
S12           6       S8 (S) S9
S13           3       S6 AND S9
S14           1       S6 AND S8
S15           2       S2 (S) S9
```